



VSR Lock, Inc.® TAMPER PROOF KEY RINGS

www.vsrlock.com

- ◆ Prevents key removal
- ◆ Not resealable if opened
- ◆ Replaces welded rings
- ◆ Serialized to identify rings and prevent substitutions
- ◆ 4 mm stainless steel

Seal key rings in seconds and prevent undetected key removals or substitutions. If forced open, the seal is destroyed showing that the ring has been tampered with. A serialized number on each ring prevents ring substitution. The 4 mm diameter ring and seal permits smooth movement of keys around the ring. Save time with portable tools that go to the job site. Eliminate the costly practice of welding or brazing key rings, which can be resealed without detection and make a ring brittle and subject to breaking.



5K 54650
Each ring has a unique serial #

DESCRIPTION	KEY CAPACITY	SOLID RING	FLEXIBLE RING
1" (3cm) Diameter	14	279	279F
1 5/8" (4cm) Diameter	22	278	278F
2" (5cm) Diameter	30	270	270F
3" (7cm) Diameter	46	277	277F
4" (9cm) Diameter	66	272	272F

Flexible rings are available in custom and larger sizes.

SEALING TOOLS	ITEM
Ring Closer	271V
Ring Crimper	271D
Ring Cutter	271X

Sealing Tools

You control who seals rings!

